

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	70 43	bar psi
VF540/ 65R30 NRO	DW18L DW20B	550 21.7	1464 57.6	641 25.3	4323 170.2	158D	0.8	5700	2660	2480	2480	2260	1.6	3470	
							12	12560	5860	5460	5460	4980	23	7640	
							1.2	7250	3380	3150	3150	2870	2	4410	
							17	15970	7440	6940	6940	6320	29	9710	
							1.4	7940	3700	3450	3450	3140	2.2	4830	
							20	17490	8150	7600	7600	6920	32	10640	
							1.6	8580	4000	3730	3730	3390	2.4	5220	
							23	18900	8810	8220	8220	7470	35	11500	
							2	9780	4550	4250	4250	3870	2.8	5950	
29	21540	10020	9360	9360	8520	41	13110								

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards