

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)																																																											
		SW	OD					MIXED APPLICATION				CYCLIC*																																																							
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar	static	10	20	25 to 65	70	bar	30																																																	
VF650/ 65R42 NRO	DW23B DW21B DW20	650	1913	847	5649	174D	174D	0.8	9020	4200	3920	3920	3570	1.6	5490																																																				
																25.6	75.3	33.4	222.4	12	19870	9250	8630	8630	7860	23	12090																																								
																												1.2	11430	5330	4970	4970	4520	2	6960																																
																																				17	25180	11740	10950	10950	9960	29	15330																								
																																												1.6	13520	6300	5880	5880	5350	2.4	8230																
																																																				23	29780	13880	12950	12950	11780	35	18130								
																																																												2	15410	7180	6700	6700	6100	2.8	9380

* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards