

FARMAX HPT



FEATURE

Lug Tip Step

BENEFIT

Increase the grip and reducing the tractor slip

FEATURE

Lug base tie bar

BENEFIT

Additional support to lugs and also helps to remove mud from lugs

FEATURE

Extra wide tread

BENEFIT

Wider footprint provides increased stability

FEATURE

50° lug angle at centre

BENEFIT

Smoother road driving comfort, less noise and vibration

FEATURE

Rounder shoulder

BENEFIT

Provides less soil damage
Better Grip


FEATURE

Deeper Tread Depths

BENEFIT

Provides improved traction and gripping power longer tire life

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)																							
		SW	OD					Speed, km/h (mph)																							
								Tractor application																							
		mm/in	mm/in					mm/in	mm/in	speed symbol	bar	Static	10	20	30	40	50	65													
650/ 75R38	DW20B DW21B DW23B	660	1941	873	5793	169D/ 172A8	228.1	speed symbol	bar	psi	Static	10	20	30	40	50	65	6	12	19	25	31	40	0.8	6990	4560	3740	3500	3330	3190	3040
																								12	15400	10040	8240	7710	7330	7030	6700
																								1.2	8880	5790	4750	4440	4230	4050	3860
																								17	19560	12750	10460	9780	9320	8920	8500
																								1.6	10510	6860	5620	5260	5000	4800	4570
																								23	23150	15110	12380	11590	11010	10570	10070
																								2.0	11980	7820	6410	5990	5700	5470	5210
																								29	26390	17220	14120	13190	12560	12050	11480
																								2.4	13340	8700	7490	6670	6350	6090	5800
35	29380	19160	16500	14690	13990	13410	12780																								

All tires confirms ETRTO T&RA & STRO standards