

# TORQUEMAX



**FEATURE**

- Stepped lug design

**BENEFIT**

- Better Grip

**FEATURE**

- Tilted lug tip

**BENEFIT**

- Lower vibration at high speeds.

**FEATURE**

- Strong & wider lugs

**BENEFIT**

- Provides higher contact area leading to higher life

**FEATURE**

- Wider tread width

**BENEFIT**

- Lower Compaction

**FEATURE**

- Lower lug angle at the shoulder

**BENEFIT**

- Better traction

**FEATURE**

- Rounder shoulder

**BENEFIT**

- Lesser soil/crop damage


**FEATURE**

- Steel belted radial construction

**BENEFIT**

- Protection from Punctures

## MACHINERY



### High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)						
		SW	OD					MIXED APPLICATION					CYCLIC*	
								mm/in	mm/in	static	10 6	20 12	25 to 65 15 to 40	bar psi
IF 850 75R42 CFO SB*	DW27B DW30B DW28B	857 33.7	2308 90.9	1009 39.7	6779 266.9	186D	0.8	14580	7930	6500	6340	1	9830	
							12	32110	17470	14320	13960	15	21650	
							1	16610	9030	7400	7220	1.25	11190	
							15	36590	19890	16300	15900	18	24650	
							1.2	18470	10040	8230	8030	1.5	12450	
							17	40680	22110	18130	17690	22	27420	
							1.4	20220	10990	9010	8790	1.75	13620	
							20	44540	24210	19850	19360	25	30000	
							1.6	21850	11880	9740	9500	2	14730	
23	48130	26170	21450	20930	29	32440								

\* SB - Steel belted Note:- for NRO rim please increase 0.2 bar on standard pressure

All tires confirms ETRTO T&RA & STRO standards