

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Static	Recommend load, kg (lbs)						
		SW	OD	Radius	mm	Speed			Constant load				Cyclic operation		
		mm	mm	mm	mm	bar			10	20	30	40	50	10	15
		in	in	in	in	psi			6	12	19	25	31	6	9
380/ 75R20	W9	380	1078	485	3183	148 A8/B	1.6	4230	2300	2010	1910	1840	1840	2760	2470
							23	9320	5070	4430	4210	4050	4050	6080	5440
	W10						2.0	4830	2630	2290	2180	2100	2100	3150	2810
							29	10640	5790	5040	4800	4630	4630	6940	6190
	3.0						6120	3330	2900	2770	2660	2660	3990	3560	
	44						13480	7330	6390	6100	5860	5860	8790	7840	
	4						7250	3940	3430	3280	3150	3150	4730	4220	
	58						15970	8680	7560	7220	6940	6940	10420	9300	