

# LOADPRO



**FEATURE**

Greater lug overlap and more lugs in footprint

**BENEFIT**

Uniform load distribution

**FEATURE**

Extra reinforced Sidewalls

**BENEFIT**

Additional lateral stability


**FEATURE**

Strong bead

**BENEFIT**

Better carcass strength and load carrying capacity

## MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius				Speed, km/h (mph)							
		mm	mm	mm	mm	mm	bar	Constant load				Cyclic operation			
		in	in	in	in	in	psi	Static	10	20	30	40	50	10	15
500/ 70R28	W15L	503	1411	667	4211	164 A8/B	1.6	6740	3660	3190	3050	2930	2930	4400	3930
							23	14850	8060	7030	6720	6450	6450	9690	8660
							2.2	8120	4410	3850	3670	3530	3530	5300	4730
	W16L	19.8	55.6	26.3	166		32	17890	9710	8480	8080	7780	7780	11670	10420
							2.6	8950	4860	4240	4050	3890	3890	5840	5210
							38	19710	10700	9340	8920	8570	8570	12860	11480
	W18L						3.0	9730	5290	4610	4400	4230	4230	6350	5670
							44	21430	11650	10150	9690	9320	9320	13990	12490
							4	11500	6250	5450	5200	5000	5000	7500	6700
						58	25330	13770	12000	11450	11010	11010	16520	14760	