FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

| Size | LI/SS | Туре | Rim | Unloaded Dimension | | SLR | RC | Infl. Press | Speed kmph /mph | | | | | |
|-----------|----------|------|---------------------|--------------------|--------------|-------------|---------------|-------------|--------------------------|------|------|------|------|------|
| | | | | SW | OD | δLN | nu | IIII. Fress | Static | 10 | 20 | 30 | 40 | 50 |
| | | | | | | | | | otatio | 6 | 12 | 19 | 25 | 31 |
| | | | | mm | mm | mm | mm | bar | Recommend load kg /lbs | | | | | |
| | | | | in | in | in | in | psi | neconinicia loda ky / bs | | | | | |
| 420/85R38 | 144 A8/B | TL | W15L W14L W13 | 450 17.7 | 1680 66.1 | 775 30.5 | 5026 197.9 | 0.8 | 4300 | 2810 | 2300 | 2000 | 1870 | 1870 |
| | | | | | | | | 12 | 9470 | 6190 | 5070 | 4410 | 4120 | 4120 |
| | | | | | | | | 1 | 4900 | 3200 | 2620 | 2280 | 2130 | 2130 |
| | | | | | | | | 15 | 10790 | 7050 | 5770 | 5020 | 4690 | 4690 |
| | | | | | | | | 1.3 | 5700 | 3720 | 3050 | 2650 | 2480 | 2480 |
| | | | | | | | | 19 | 12560 | 8190 | 6720 | 5840 | 5460 | 5460 |
| | | | | | | | | 1.6 | 6440 | 4200 | 3440 | 3000 | 2800 | 2800 |
| | | | | | | | | 23 | 14190 | 9250 | 7580 | 6610 | 6170 | 6170 |

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards