

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD	JLN	nu	IIII. FICSS	Static	10	20	30	40	50
									Otatio	6	12	19	25	31
				mm	mm	mm	mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi						
320/85R36	128 A8/B	H	W11 W10 W9	325 12.8	1458 57.4	677 26.7	4380 172.4	0.8	2760	1800	1480	1280	1200	1200
								12	6080	3960	3260	2820	2640	2640
								1	3150	2060	1690	1470	1370	1370
								15	6940	4540	3720	3240	3020	3020
								1.3	3660	2390	1960	1700	1590	1590
								19	8060	5260	4320	3740	3500	3500
								1.6	4140	2700	2210	1930	1800	1800
								23	9120	5950	4870	4250	3960	3960

All tires confirms ETRTO T&RA & STRO standards