

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
320/85R32	142A8/B	TL	W11 W10 W9	325 12.8	1357 53.4	627 24.7	4062 160	3	5150	3360	2760	2400	2240	2240
								44	11340	7400	6080	5290	4930	4930
								3.4	5540	3620	2960	2580	2410	2410
								49	12200	7970	6520	5680	5310	5310
								3.8	5910	3860	3160	2750	2570	2570
								55	13020	8500	6960	6060	5660	5660
								4	6100	3980	3260	2840	2650	2650
								58	13440	8770	7180	6260	5840	5840