

FARMAX R85

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph /mph					
				sw	OD mm	mm	mm	IIII. FI633	Static	10	20	30	40	50
										6	12	19	25	31
				mm				bar	Recommend load kg /lbs					
				in	in	in	in	psi	necomment toda kg / lbs					
380/85R30	135 A8/B	F	W12 W13 W11	385 15.2	1408 55.4	646 25.4	4195 165.2	0.8	3340	2180	1780	1550	1450	1450
								12	7360	4800	3920	3410	3190	3190
								1	3820	2490	2040	1780	1660	1660
								15	8410	5480	4490	3920	3660	3660
								1.3	4440	2900	2370	2070	1930	1930
								19	9780	6390	5220	4560	4250	4250
								1.6	5010	3270	2680	2330	2180	2180
								23	11040	7200	5900	5130	4800	4800 /

All tires confirms ETRTO T&RA & STRO standards