

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

| Size | LI/SS | Type | Rim | Unloaded Dimension | | SLR | RC | Infl. Press | Speed kmph /mph | | | | | |
|-----------|---------|------|------------------|--------------------|------|-----|------|-------------|------------------------|------|------|------|------|------|
| | | | | SW | OD | | | | Static | 10 | 20 | 30 | 40 | 50 |
| | | | | mm | mm | | | | | 6 | 12 | 19 | 25 | 31 |
| | | | | in | in | | | | Recommend load kg /lbs | | | | | |
| 320/85R28 | 124A8/B | TL | W11 W10 W9 | 330 | 1255 | 574 | 3698 | 0.8 | 2460 | 1610 | 1320 | 1140 | 1070 | 1070 |
| | | | | | | | | 12 | 5420 | 3550 | 2910 | 2510 | 2360 | 2360 |
| | | | | | | | | 1 | 2810 | 1830 | 1500 | 1310 | 1220 | 1220 |
| | | | | | | | | 15 | 6190 | 4030 | 3300 | 2890 | 2690 | 2690 |
| | | | | | | | | 1.3 | 3270 | 2130 | 1750 | 1520 | 1420 | 1420 |
| | | | | | | | | 19 | 7200 | 4690 | 3850 | 3350 | 3130 | 3130 |
| | | | | | | | | 1.6 | 3680 | 2400 | 1970 | 1710 | 1600 | 1600 |
| | | | | | | | | 23 | 8110 | 5290 | 4340 | 3770 | 3520 | 3520 |