FARMAX R85



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc \bigcirc • Wider tread BENEFITS

Tractor

| Size | LI/SS | Туре | Rim | Unloaded Dimension | | SLR | RC | Infl. Press | Speed kmph /mph | | | | | |
|-----------|----------|------|---------------------|--------------------|------|------|-------|-------------|---------------------------|------|------|------|------|------|
| | | | | SW | OD | δLN | ΠŪ | IIII. Fress | Static | 10 | 20 | 30 | 40 | 50 |
| | | | | | | | | | olallo | 6 | 12 | 19 | 25 | 31 |
| | | | | mm | mm | mm | mm | bar | Recommend load kg /lbs | | | | | |
| | | | | in | in | in | in | psi | neconinienu toau ky / ibs | | | | | |
| 420/85R24 | 137 A8/B | TL | W15L W14L W13 | | | | | 0.8 | 3520 | 2300 | 1880 | 1640 | 1530 | 1530 |
| | | | | | | | | 12 | 7750 | 5070 | 4140 | 3610 | 3370 | 3370 |
| | | | | | | | | 1 | 4030 | 2630 | 2150 | 1870 | 1750 | 1750 |
| | | | | 450 | 1324 | 597 | 3906 | 15 | 8880 | 5790 | 4740 | 4120 | 3850 | 3850 |
| | | | | 17.7 | 52.1 | 23.5 | 153.8 | 1.3 | 4690 | 3060 | 2510 | 2180 | 2040 | 2040 |
| | | | | | | | | 19 | 10330 | 6740 | 5530 | 4800 | 4490 | 4490 |
| | | | | | | | | 1.6 | 5290 | 3450 | 2830 | 2460 | 2300 | 2300 |
| | | | | | | | | 23 | 11650 | 7600 | 6230 | 5420 | 5070 | 5070 |

Reduced soil compactionIncreased footprint

All tires confirms ETRTO T&RA & STRO standards