

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
									Static	25	40	50	65	bar	10	15
				mm	mm				16	25	31	40	psi	6	9	
540/65R30	150D	TL	W16L W18L	550 21.7	1464 57.6	666 26	4338 170.8	0.8	2020	2090	1930	1850	1760	1	2990	2730
								12	4450	4600	4250	4070	3880	15	6590	6010
								1	2310	2380	2200	2110	2010	1.25	3420	3120
								15	5090	5240	4850	4650	4430	18	7530	6870
								1.3	2690	2770	2560	2460	2340	263	3980	3630
								19	5930	6100	5640	5420	5150	3811	8770	8000
								2.4	3850	3970	3670	3520	3350	3	5700	5190
								35	8480	8740	8080	7750	7380	44	12560	11430

All tires confirms ETRTO T&RA & STRO standards