

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
480/65R24	133D	TL	W15L W14L	480 18.9	1234 48.6	558 22	3644 143.5	0.8	1580	1620	1500	1440	1370	1	2330	2120
								12	3480	3570	3300	3170	3020	15	5130	4670
								1	1790	1850	1710	1640	1560	1.25	2650	2420
								15	3940	4070	3770	3610	3440	18	5840	5330
								1.3	2090	2160	1990	1910	1820	1.63	3090	2820
								19	4600	4760	4380	4210	4010	24	6810	6210
								1.6	2370	2440	2260	2160	2060	2	3500	3190
								23	5220	5370	4980	4760	4540	29	7710	7030

All tires confirms ETRTO T&RA & STRO standards