

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
440/ 65R24	128D	TL	W13 W14L W15L	441	1182	540	3565	0.8	1370	1410	1300	1250	1190	1	2020	1840
								12	3020	3110	2860	2750	2620	15	4450	4050
								1.0	1560	1610	1490	1430	1360	1.25	2310	2110
								15	3440	3550	3280	3150	3000	18	5090	4650
								1.4	1910	1970	1820	1740	1660	1.75	2820	2570
								20	4210	4340	4010	3830	3660	25	6210	5660
								1.6	2070	2130	1970	1890	1800	2	3060	2790
								23	4560	4690	4340	4160	3960	29	6740	6150

All tires confirms ETRTO T&RA & STRO standards