

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar psi	10	15
650/ 65R42	158D	TL	W18, DW20BL DW21B	645	1913	885	5775	0.8	3250	3350	3100	2970	2830	1	4810	4390
				12	7160			7380	6830	6540	6230	15	10590	9670		
				1.0	3710			3830	3540	3390	3230	1.25	5490	5010		
				1.5	8170			8440	7800	7470	7110	18	12090	11040		
				1.3	4320			4460	4120	3950	3760	1.63	6390	5830		
				1.9	9520			9820	9070	8700	8280	24	14070	12840		
				1.6	4890			5040	4650	4460	4250	2	7230	6590		
				2.3	10770			11100	10240	9820	9360	29	15930	14520		

All tires confirms ETRTO T&RA & STRO standards