

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
									Recommend load kg /lbs					
520/70R34	148 A8/B	TL	W15L	530	1640	746	4864	0.8	4830	3150	2580	2250	2100	2100
								12	10640	6940	5680	4960	4630	4630
			W16L					1	5500	3590	2940	2560	2390	2390
								15	12110	7910	6480	5640	5260	5260
			W18L					1.3	6420	4190	3430	2990	2790	2790
								19	14140	9230	7560	6590	6150	6150
			1.6					7250	4730	3870	3370	3150	3150	
			23					15970	10420	8520	7420	6940	6940	