

FARMAX R70

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	RIm	Unloaded Dimension					Speed kmph /mph					
				sw	OD mm	SLR mm	RC	Infl.Press	Static	10	20	30	40	50
										6	12	19	25	31
				mm			mm	bar	Recommend load kg /lbs					
				in	in	in	in	psi		110	Ticooninicia load kg / lbs			
480/70R34	149 A8/B	TL	W14L W15L W16L	490 19.3	1580 62.2	722 28.4	4698 185	1.8	6330	4130	3380	2940	2750	2750
								26	13940	9100	7440	6480	6060	6060
								2	6720	4380	3590	3120	2920	2920
								29	14800	9650	7910	6870	6430	6430
								2.2	7110	4640	3800	3310	3090	3090
								32	15660	10220	8370	7290	6810	6810
								2.4	7480	4880	3610	3480	3250	3250
								35	16480	10750	7950	7670	7160	7160

All tires confirms ETRTO T&RA & STRO standards