FARMAX R70



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc • Wider tread BENEFITS

Tractor

 \bigcirc

Size	LI/SS	Туре	Rim	Unloaded Dimension					Speed kmph /mph					
				SW mm	OD mm	SLR mm	RC mm	Infl.Press	Static	10	20	30	40	50
								bar		6 12 19 25 31				
				in	in	in	in	psi		Recommend load kg /lbs				
480/70R34	143 A8/B	TL	W14L W15L W16L	490 19.3	1580 62.2	722 28.4	4698 185	0.8	4190	2730	2240	1950	1820	1820
								12	9230	6010	4930	4300	4010	4010
								1	4760	3110	2550	2210	2070	2070
								15	10480	6850	5620	4870	4560	4560
								1.3	5540	3620	2960	2580	2410	2410
								19	12200	7970	6520	5680	5310	5310
								1.6	6270	4090	3350	2920	2725	2725
								23	13810	9010	7380	6430	6000	6000 /

 Reduced soil compaction · Increased footprint

All tires confirms ETRTO T&RA & STRO standards