

# FARMAX R70

## FEATURE

• Greater lug overlap

## **BENEFITS**

- More lugs in footprint
- Better stability

## FEATURE

• Larger inner volume

#### **BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



## FEATURE

Wider tread

#### BENEFITS

- Reduced soil compaction
- Increased footprint

#### **FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

#### **BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

## FEATURE

• Rounded shoulder

#### BENEFIT

• Less soil disturbance


## FEATURE

• Dual lug angle

## BENEFITS

- Superior traction
- Better Roadability

## MACHINERY



Tractor

| Size      | LI/SS    | Туре | RIm   | Unloaded Dimension |       |       |       |            | Speed kmph /mph |                        |      |      |      |        |
|-----------|----------|------|-------|--------------------|-------|-------|-------|------------|-----------------|------------------------|------|------|------|--------|
|           |          |      |       | sw                 | OD    | SLR   | RC    | Infl.Press | Static          | 10                     | 20   | 30   | 40   | 50     |
|           |          |      |       |                    |       |       |       |            |                 | 6                      | 12   | 19   | 25   | 31     |
|           |          |      |       | mm                 | mm    | mm    | mm    | bar        |                 | Recommend load kg /lbs |      |      |      |        |
|           |          |      |       | in                 | in    | in    | in    | psi        |                 |                        |      |      |      |        |
| 600/70R30 | 152 A8/B | TL   |       |                    |       |       | 0.8   | 5430       | 3540            | 2900                   | 2530 | 2360 | 2360 |        |
|           |          |      |       |                    |       |       |       | 12         | 11960           | 7800                   | 6390 | 5570 | 5200 | 5200   |
|           |          |      |       |                    |       |       |       | 1          | 6190            | 4040                   | 3310 | 2880 | 2690 | 2690   |
|           |          |      | DW18L | 611                | 1602  | 717   | 4681  | 15         | 13630           | 8900                   | 7290 | 6340 | 5930 | 5930   |
|           |          |      | DW20B | 24.06              | 63.07 | 28.25 | 184.3 | 1.3        | 7220            | 4710                   | 3860 | 3360 | 3140 | 3140   |
|           |          |      |       |                    |       |       |       | 19         | 15900           | 10370                  | 8500 | 7400 | 6920 | 6920   |
|           |          |      |       |                    |       |       |       | 1.6        | 8170            | 5330                   | 3940 | 3800 | 3550 | 3550   |
|           |          |      |       |                    |       |       |       | 23         | 18000           | 11740                  | 8680 | 8370 | 7820 | 7820 / |

All tires confirms ETRTO T&RA & STRO standards