FARMAX R70



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc • Wider tread BENEFITS

Tractor

 \bigcirc

Size	LI/SS	Туре	Rim	Unloaded Dimension					Speed kmph /mph					
				SW	OD	SLR mm	RC mm	Infl.Press	Static	10 6	20 12	30 19	40 25	50 31
				mm	mm			bar						
				in	in	in	in	psi	Recommend load kg /lbs					
480/70R30	147D/150A8	TL	W14L W15L W16L	490 19.3	1478 58.2	671 26.4	4377 172.3	1.5	5380	3510	2880	2500	2560	2460
								22	11850	7730	6340	5510	5640	5420
								1.8	5980	4280	3200	2780	2850	2730
								26	13170	9430	7050	6120	6280	6010
								2	6350	4530	3390	2950	3020	2900
								29	13990	9980	7470	6500	6650	6390
								2.4	7070	4610	3780	3540	3370	3230
								35	15570	10150	8330	7800	7420	7110

 Reduced soil compaction · Increased footprint

All tires confirms ETRTO T&RA & STRO standards