

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl.Press	Speed kmph /mph					
				SW	OD				Static	10	20	30	40	50
				mm	mm					6	12	19	25	31
				in	in				Recommend load kg /lbs					
600/70R28	161 A8/B	TL	DW18L DW20B	611 24.1	1551 61.1	692 27.2	4532 178.4	1.8	8210	5360	4390	3820	3570	3570
								26	18080	11810	9670	8410	7860	7860
								2	8740	5700	4670	4070	3800	3800
								29	19250	12560	10290	8960	8370	8370
								2.4	9730	6350	5200	4530	4230	4230
								35	21430	13990	11450	9980	9320	9320
								2.8	10640	6940	5130	4950	4625	4625
								41	23440	15290	11300	10900	10190	10190