## FARMAX R70



## FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE $\bigcirc$ • Wider tread BENEFITS

Tractor

 $\bigcirc$ 

Size	LI/SS	Туре	Rim	Unloaded Dimension					Speed kmph /mph					
				SW	OD	SLR mm	RC mm	Infl.Press	Static	10 6	20 12	30 19	40 25	50 31
				mm	mm			bar						
				in	in	in	in	psi	Recommend load kg /lbs					
480/70R28	151A8/B	TL	W14L W15L W16L	490 19.3	1421 55.9	643 25.3	4200 165.4	2	6030	3930	3220	2800	2620	2620
								29	13280	8660	7090	6170	5770	5770
								2.4	6690	4370	3580	3110	2910	2910
								35	14740	9630	7890	6850	6410	6410
								2.8	7340	4790	3920	3410	3190	3190
								41	16170	10550	8630	7510	7030	7030
								3.2	7940	5180	4240	3690	3450	3450
								46	17490	11410	9340	8130	7600	7600 /

 Reduced soil compaction · Increased footprint

All tires confirms ETRTO T&RA & STRO standards