

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
									Recommend load kg /lbs					
480/70R24	138 A8/B	TL	W14L	490	1316	591	3871	0.8	3610	2360	1930	1680	1570	1570
								12	7950	5200	4250	3700	3460	3460
								1	4120	2690	2200	1920	1790	1790
								15	9070	5930	4850	4230	3940	3940
								1.3	4810	3140	2570	2240	2090	2090
								19	10590	6920	5660	4930	4600	4600
1.6	5430	3540	2900	2530	2360	2360								
23	11960	7800	6390	5570	5200	5200								