FARMAX R70



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc • Wider tread BENEFITS

Tractor

 \bigcirc

Size	LI/SS	Туре	Rim	Unloaded Dimension					Speed kmph /mph					
				SW	OD mm	SLR mm	RC mm	Infl.Press	Static	10 6	20 12	30 19	40 25	50 31
				mm				bar						51
				in	in	in	in	psi		Recommend load kg /lbs				
380/70R20	132 A8/B	TL	W13 W12 W11	380 15	1082 42.6	486 19.2	3185 125.4	1.3	3220	2100	1720	1500	1400	1400
								19	7090	4630	3790	3300	3080	3080
								1.6	3630	2370	1940	1690	1580	1580
								23	8000	5220	4270	3720	3480	3480
								2	4140	2700	2210	1930	1800	1800
								29	9120	5950	4870	4250	3960	3960
								2.4	4600	3000	2460	2140	2000	2000
								35	10130	6610	5420	4710	4410	4410 /

 Reduced soil compaction · Increased footprint

All tires confirms ETRTO T&RA & STRO standards