

FARMAX R70

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance

FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	Rim	Unloaded Dimension		21.5			Speed kmph /mph					
				sw	OD	SLR	RC	Infl.Press	Static	10	20	30	40	50
										6	12	19	25	31
				mm	mm	mm	mm	bar		Recommend load kg /lbs				
				in	in	in	in	psi						
300/70R20	110 A8/B	Ħ					0.8	1630	1070	870	760	710	710	
								12	3590	2360	1920	1670	1560	1560
								1	1860	1220	1000	870	810	810
			W9	295	952	434	2826	15	4100	2690	2200	1920	1780	1780
			W10	11.6	37.5	17.1 1	111.3	1.3	2160	1410	1160	1010	940	940
								19	4760	3110	2560	2220	2070	2070
								1.6	2440	1590	1300	1130	1060	1060
								23	5370	3500	2860	2490	2330	2330 /

All tires confirms ETRTO T&RA & STRO standards