FARMAX R70



FEATURE • Greater lug overlap **FEATURES** BENEFITS • Reduced space between lugs • Mud breaker at the centre • More lugs in footprint Better stability **BENEFITS** Better roadability · Increased service life • Self cleaning FEATURE • Larger inner volume FEATURE BENEFITS · Rounded shoulder • Reduced soil compaction BENEFIT Increased load · Less soil disturbance carrying capacity FEATURE • Dual lug angle **BENEFITS** MACHINERY Superior traction Better Roadability FEATURE \bigcirc • Wider tread BENEFITS

Tractor

 \bigcirc

Size	LI/SS	Туре	RIm	Unloaded Dimension					Speed kmph /mph					
				SW mm	OD mm	SLR mm	RC mm	Infl.Press	Static	10	20	30	40	50 31
								bar		6				
				in	in	in	in	psi	Recommend load kg /lbs					
380/70R24	125 A8/B	TL	W13 W12 W11	380 15	1190 46.9	540 21.3	3523 138.7	0.8	2530	1650	1350	1180	1100	1100
								12	5570	3630	2970	2600	2420	2420
								1	2880	1880	1540	1340	1250	1250
								15	6340	4140	3390	2950	2750	2750
								1.3	3360	2190	1800	1560	1460	1460
								19	7400	4820	3960	3440	3220	3220
								1.6	3800	2480	2030	1770	1650	1650
								23	8370	5460	4470	3900	3630	3630 /

 Reduced soil compaction · Increased footprint

All tires confirms ETRTO T&RA & STRO standards