

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

| Size      | LI/SS      | Rim      | Unloaded Dimension |              | SLR         | RC            | Infl. Press | Speed, km/h (mph)      |      |      |      |      |      |      |
|-----------|------------|----------|--------------------|--------------|-------------|---------------|-------------|------------------------|------|------|------|------|------|------|
|           |            |          | SW                 | OD           |             |               |             | Field                  | 10   | 25   | 30   | 40   | 50   | 65   |
|           |            |          | mm/in              | mm/in        |             |               |             |                        | 6    | 16   | 19   | 25   | 31   | 40   |
| 230/95R36 | 130D/133A8 | W8<br>W7 | 228<br>9           | 1352<br>53.2 | 633<br>24.9 | 4035<br>158.9 | bar         | maximum Load, kg (lbs) |      |      |      |      |      |      |
|           |            |          |                    |              |             |               | psi         |                        |      |      |      |      |      |      |
|           |            |          |                    |              |             |               | 3.4         | 1830                   | 2390 | 1880 | 1740 | 1670 | 1590 | 1450 |
|           |            |          |                    |              |             |               | 49          | 4030                   | 5260 | 4140 | 3830 | 3680 | 3500 | 3190 |
|           |            |          |                    |              |             |               | 3.6         | 1900                   | 2480 | 1960 | 1810 | 1730 | 1650 | 1500 |
|           |            |          |                    |              |             |               | 52          | 4190                   | 5460 | 4320 | 3990 | 3810 | 3630 | 3300 |
|           |            |          |                    |              |             |               | 4           | 2010                   | 2630 | 2070 | 1920 | 1840 | 1750 | 1590 |
|           |            |          |                    |              |             |               | 58          | 4430                   | 5790 | 4560 | 4230 | 4050 | 3850 | 3500 |
|           |            |          |                    |              |             |               | 4.2         | 2070                   | 2700 | 2130 | 1970 | 1890 | 1800 | 1640 |
|           |            |          |                    |              |             |               | 61          | 4560                   | 5950 | 4690 | 4340 | 4160 | 3960 | 3610 |
|           |            |          |                    |              |             |               | 4.4         | 2130                   | 2780 | 2190 | 2030 | 1940 | 1850 | 1680 |
|           |            |          |                    |              |             |               | 64          | 4690                   | 6120 | 4820 | 4470 | 4270 | 4070 | 3700 |
| 4.6       | 2190       | 2850     | 2250               | 2080         | 2000        | 1900          | 1730        |                        |      |      |      |      |      |      |
| 67        | 4820       | 6280     | 4960               | 4580         | 4410        | 4190          | 3810        |                        |      |      |      |      |      |      |

All tires confirms ETRTO T&RA & STRO standards