

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)						
			SW	OD				Field	10	25	30	40	50	65
			mm/in	mm/in					mm/in	mm/in	bar	maximum Load, kg (lbs)		
270/95R44 (11.2R44)	142D/145A8	W9 W8 W10	275 10.8	1632 64.3	765 30.1	4948 194.8	2.8	2330	3050	2410	2220	2130	2030	1850
							41	5130	6720	5310	4890	4690	4470	4070
							3.6	2700	3530	2780	2570	2470	2350	2140
							52	5950	7780	6120	5660	5440	5180	4710
							4	2880	3750	2960	2740	2630	2500	2280
							58	6340	8260	6520	6040	5790	5510	5020
							4.4	3050	3980	3140	2900	2780	2650	2410
							64	6720	8770	6920	6390	6120	5840	5310

All tires confirms ETRTO T&RA & STRO standards