

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)							
			SW	OD				Field	10	25	30	40	50	65	
			mm/in	mm/in					6	16	19	25	31	40	
270/95R38 (11.2R38)	140D/143A8	W9 W8 W10	275 10.8	1479 58.2	689 27.1	4507 177.4	bar	2.8	2140	2790	2200	2040	1950	1860	1690
							psi	41	4710	6150	4850	4490	4300	4100	3720
								3.6	2480	3240	2560	2370	2270	2160	1970
								52	5460	7140	5640	5220	5000	4760	4340
								4	2650	3450	2730	2520	2420	2300	2090
								58	5840	7600	6010	5550	5330	5070	4600
								4.6	2880	3750	2960	2740	2630	2500	2280
								67	6340	8260	6520	6040	5790	5510	5020

All tires confirms ETRTO T&RA & STRO standards