

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
									Recommend load kg /lbs					
520/85R46	158 A8/B	TL	DW16L	530	2052	939	6109	0.8	6510	4250	3480	3030	2830	2830
				20.9	80.8	37	240.5	12	14340	9360	7670	6670	6230	6230
			DW18L	530	2052	939	6109	1	7430	4850	3970	3460	3230	3230
				20.9	80.8	37	240.5	15	16370	10680	8740	7620	7110	7110
			DW18L	530	2052	939	6109	1.3	8650	5640	4620	4020	3760	3760
				20.9	80.8	37	240.5	19	19050	120420	10180	8850	8280	8280
			DW18L	530	2052	939	6109	1.6	9780	6380	5230	4550	4250	4250
				20.9	80.8	37	240.5	23	21540	14050	11520	10020	9360	9360

All tires confirms ETRTO T&RA & STRO standards