

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg /lbs						
210/95R32 (8.3 R 32)	117D/ 120A8	TL	W7 W6	214 8.4	1213 47.8	567 22.3	3696 145.5	2	1130	1470	1160	1070	1030	980	890
								29	2490	3240	2560	2360	2270	2160	1960
								2.4	1250	1640	1290	1190	1140	1090	990
								35	2750	3610	2840	2620	2510	2400	2180
								3	1430	1860	1470	1360	1300	1240	1130
								44	3150	4100	3240	3000	2860	2730	2490
								3.2	1480	1930	1520	1410	1350	1285	1170
								46	3260	4250	3350	3110	2970	2830	2580