

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm in	mm in					mm in	mm in	bar psi	6	16	25
270/95R42 (11.2R42)	137D/ 140A8	TL	W8 W9 W10	275 10.8	1581 62.2	740 29.1	4793 188.7	2.8	2290	2990	2360	2180	2090	1990	1810
								41	5040	6590	5200	4800	4600	4380	3990
								3.2	2470	3230	2550	2350	2260	2150	1960
								46	5440	7110	5620	5180	4980	4740	4320
								3.6	2650	3450	2730	2520	2420	2300	2090
52	5840	7600	6010	5550	5330	5070	4600								

All tires confirms ETRTO T&RA & STRO standards