

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm	mm					6	16	25	31	40	50
				in	in				Recommend load kg /lbs						
230/95R44	134D/ 137A8	TL	W8 W9 W10	228 9	1556 61.3	735 28.9	4812 189.5	3.6	2120	2760	2180	2010	1930	1840	1670
								52	4670	6080	4800	4430	4250	4050	3680
								3.8	2190	2850	2250	2080	2000	1900	1730
								55	4820	6280	4960	4580	4410	4190	3810
								4.2	2310	3020	2380	2200	2110	2010	1830
								61	5090	6650	5240	4850	4650	4430	4030
								4.6	2440	3180	2510	2320	2230	2120	1930
								67	5370	7000	5530	5110	4910	4670	4250