

# FARMAX R85

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)						
			SW	OD				Static	10	20	30	40	50	65
			mm/in	mm/in					6	12	19	25	31	40
340/85 R46	150D/153 A8	W11 W12	343 13.5	1746 68.7	816 32.1	5310 209	bar	maximum Load, kg (lbs)						
							psi							
							3.2	3380	4410	3480	3220	3090	2940	2680
							46	7440	9710	7670	7090	6810	6480	5900
							3.6	3620	4730	3730	3450	3310	3150	2870
							52	7970	10420	8220	7600	7290	6940	6320
4	3850	5030	3970	3670	3520	3350	3050							
58	8480	11080	8740	8080	7750	7380	6720							