

FARMAX R70

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)						
		SW	OD					Static	10	25	40	50	65	70
		mm/in	mm/in											
580/70R42	W18L	597 22.7	1895 74.0	859 33.8	5578 219.6	158D/ 161A8	0.8	6510	4250	3350	3100	2970	2830	2580
							12	14340	9360	7380	6830	6540	6230	5680
							1.2	8260	5390	4250	3930	3770	3590	3270
							17	18190	11870	9360	8660	8300	7910	7200
							1.4	9040	5900	4660	4300	4130	3930	3580
							20	19910	13000	10260	9470	9100	8660	7890
							1.6	9780	6380	5040	4650	4460	4250	3870
							23	21540	14050	11100	10240	9820	9360	8520