

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)					
				SW	OD				Speed, km/h (mph)					
				mm/in	mm/in				Static	10	20	30	40	50
										6	12	19	25	31
340/85R38	151 A8/B	TL	W11 W12	355 14.0	1543 60.7	719 28.3	4645 182.9	bar	6140	4010	3280	2860	2670	2670
								psi	13520	8830	7220	6300	5880	5880
								3.4	6600	4310	3530	3070	2870	2870
								4.9	14540	9490	7780	6760	6320	6320
								3.8	7040	4590	3760	3270	3060	3060
								5.5	15510	10110	8280	7200	6740	6740
								4	7250	4730	3870	3370	3150	3150
								5.8	15970	10420	8520	7420	6940	6940
								4.5	7940	5180	4240	3690	3450	3450
								6.5	17490	11410	9340	8130	7600	7600

All tires confirms ETRTO T&RA & STRO standards