

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					10	20	30	40 to 65	70	15	30	
IF 600/70R30	DW20, DW21	605 23.8	1602 63.1	726 28.6	4781 188.2	165D	speed	bar	10	20	30	40 to 65	70	15	30
							symbol	psi	6	12	19	25 to 40	43	9	19
							0.8	3430	2920	2810	2700	2460	3110	2960	
							1.2	7560	6430	6190	5950	5420	6850	6520	
							1.2	4340	3690	3560	3420	3110	3930	3740	
							1.7	9560	8130	7840	7530	6850	8660	8240	
							1.6	5140	4370	4210	4050	3690	4660	4430	
							2.3	11320	9630	9270	8920	8130	10260	9760	
							2.0	5870	4990	4800	4620	4200	5310	5060	
							2.9	12930	10990	10570	10180	9250	11700	11150	
							2.2	6210	5280	5090	4890	4450	5620	5350	
							3.2	13680	11630	11210	10770	9800	12380	11780	
2.4	6540	5560	5360	5150	4690	5920	5640								
3.5	14410	12250	11810	11340	10330	13040	12420								

All tires confirms ETRTO T&RA & STRO standards