

TORQUEMAX



FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life

FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction

FEATURE


- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

*Lower Compaction, Higher Traction and Better Roadability

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)							
		SW	OD					MIXED APPLICATION					CYCLIC*		
		mm/in	mm/in					10	20	30	40 to 65	70	15	30	
				mm/in	mm/in	speed symbol	bar	6	12	19	25 to 40	43	9	19	
IF 710/ 70R38	DW23B DW25B	720 28.3	1959 77.1	850 33.5	5800 228.3	178D	0.8	5000	4260	4100	3940	3590	4530	4310	
							12	11010	9380	9030	8680	7910	9980	9490	
							1.2	6350	5400	5200	5000	4550	5750	5480	
							1.7	13990	11890	11450	11010	10020	12670	12070	
							1.6	7520	6390	6160	5920	5390	6810	6480	
							23	16560	14070	13570	13040	11870	15000	14270	
							2.0	8560	7280	7010	6740	6130	7750	7380	
							29	18850	16040	15440	14850	13500	17070	16260	
							2.2	9060	7700	7420	7130	6490	8200	7810	
							32	19960	16960	16340	15700	14300	18060	17200	
							2.4	9530	8100	7800	7500	6830	8630	8210	
35	20990	17840	17180	16520	15040	19010	18080								

All tires confirms ETRTO T&RA & STRO standards