

FARMAX R80

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
480/80R46	164A8/164B	TL	DW16L	485	1940	900	5800	1.3	6830	4460	3650	3180	2970	2970
								19	15040	9820	8040	7000	6540	6540
								1.6	7710	5030	4120	3580	3350	3350
								23	16980	11080	9070	7890	7380	7380
								2	8790	5730	4700	4090	3820	3820
								29	19360	12620	10350	9010	8410	8410
								2.4	9780	6380	5230	4550	4250	4250
								35	21540	14050	11520	10020	9360	9360
								2.8	10630	6930	5680	4940	4620	4620
								29	23410	15260	12510	10880	10180	10180
3.2	11500	7500	6150	5350	5000	5000								
35	25330	16520	13550	11780	11010	11010								