

FARMAX R85

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs)						
				SW	OD				Speed, km/h (mph)						
				mm/in	mm/in				Static	10	20	30	40	50	65
									bar	psi	6	12	19	25	31
420/85R34	142D/145A8	TL	W15L W14L W13	450 17.7	1578 62.1	724 28.5	4705 185.3	0.8	4070	2660	2180	2040	1940	1860	1770
								12	8960	5860	4800	4490	3900	4100	3900
								1.2	5150	3360	2760	2580	2450	2350	2240
								17	11340	7400	6080	5680	4930	5180	4930
								1.4	5640	3680	3010	2820	2680	2570	2450
								20	12420	8110	6630	6210	5400	5660	5400
								1.6	6100	3980	3260	3050	2900	2780	2650
								23	13440	8770	7180	6720	6390	6120	5840