

# FARMAX R90

**FEATURE**

- Higher angle and lug overlap at centre

**BENEFIT**

- Better roadability

**FEATURE**

- R1-W tread depth

**BENEFIT**

- Longer tyre life

**FEATURE**

- Wider tread
- Larger inner volume

**BENEFIT**

- Reduced soil compaction



**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced damage to soil and crop


**FEATURE**

- Lower angle at shoulder

**BENEFIT**

- Superior traction

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
420/90R30	142 A8/B	TL	DW13 W14L	426	1518	684 26.92	4483 178.5	0.8	4070	2660	2180	1890	1770	1770
				12	8960			5860	4800	4160	3900	3900		
				1.2	5150			3360	2760	2400	2240	2240		
				17	11340			7400	6080	5290	4930	4930		
				1.4	5640			3680	3010	2620	2450	2450		
				20	12420			8110	6630	5770	5400	5400		
				1.6	6100			3980	3260	2840	2650	2650		
				23	13440			8770	7180	6260	5840	5840		