

TORQUEMAX

FEATURE

- Stepped lug design

BENEFIT

- Better Grip

FEATURE

- Tilted lug tip

BENEFIT

- Lower vibration at high speeds.

FEATURE

- Strong & wider lugs

BENEFIT

- Provides higher contact area leading to higher life



FEATURE

- Wider tread width

BENEFIT

- Lower Compaction

FEATURE

- Lower lug angle at the shoulder

BENEFIT

- Better traction


FEATURE

- Rounder shoulder

BENEFIT

- Lesser soil/crop damage

MACHINERY



High Powered Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl.Press	maximum Load, kg (lbs) Speed, km/h (mph)					
		SW	OD					MIXED APPLICATION					CYCLIC*
								mm/in	mm/in	mm/in	mm/in	speed symbol	bar psi
VF710/ 70R42	DW25B	720 28.3	2061 81.1	926 36.5	6100 240.1	185 D	0.8	5210	4860	4860	4420	6800	
							12	11480	10700	10700	9740	14980	
							1.2	6600	6160	6160	5610	8620	
							17	14540	13570	13570	12360	18990	
							1.6	7810	7290	7290	6630	10210	
							23	17200	16060	16060	14600	22490	
							2	8910	8310	8310	7560	11630	
							29	19630	18300	18300	16650	25620	
							2.4	9920	9250	9250	8420	12950	
							35	21850	20370	20370	18550	28520	

All tires confirms ETRTO T&RA & STRO standards