

FARMAX R85

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	Rim	Rim size in	Infl tire		Static	Rolling	Load	Infl.	Recommended load, kg (lbs)					
			dimension		Loaded	circm.			Static	Speed, km/h (mph)				
			SW	OD	radius	Index				10	20	30	40	50
			mm	mm	mm									
in	in	in	in	in	Symbol	bar	psi							
520/ 85R38	DW16L DW18L	38	530	1855	847	5513	155 A8 155 B	0.8	5930	3870	3170	2760	2580	2580
			20.9	73.0	33.3	217.1		12	13060	8520	6980	6080	5680	5680
								1.0	6760	4410	3620	3150	2940	2940
								15	14890	9710	7970	6940	6480	6480
								1.3	7890	5150	4220	3670	3430	3430
								19	17380	11340	9300	8080	7560	7560
								1.6	8910	5810	4770	4150	3875	3875
				23	19630	12800	10510	9140	8540	8540				