

FARMAX R65

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance


FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
320/ 65R18	109D	TL	W10 W9 W11	319 12.6	873 34.4	400 16	2605 103	0.8	370	380	350	340	320	1.0	540	500
								12	810	840	770	750	700	14.5	1190	1100
								1.0	900	920	850	820	780	1.3	1330	1210
								15	1980	2030	1870	1810	1720	18.1	2930	2670
								1.2	1000	1030	950	910	870	1.5	1480	1350
								17	2200	2270	2090	2000	1920	21.8	3260	2970
								1.4	1090	1130	1040	1000	950	1.8	1620	1470
								20	2400	2490	2290	2200	2090	25.4	3570	3240
								1.6	1180	1220	1130	1080	1030	2.0	1750	1600
								23	2600	2690	2490	2380	2270	29.0	3850	3520