RPG

YIELDMAX

CEAT SPECIALTY

FEATURE
- R1-W Pattern

BENEFIT
- Longer tyre life

FEATURE
- Dual Lug angle

BENEFIT
- Higher traction and better stability

FEATURE
- Higher lug overlap

BENEFIT
- Enhanced road ability and load ability

FEATURE
- Strong & sharp shoulders

BENEFIT
- Better grip

FEATURE
- Wide open shoulders

BENEFIT
- Better self cleaning

FEATURE
- Rounded Lug Base

BENEFIT
- Stubble Resistance

FEATURE
- Steel belted radial construction

BENEFIT
- Protection from Punctures

MACHINERY

Trailer

Size	Rim	Unloaded dimension SW mm in	Unloaded dimension OD mm in	Static Loaded Radius mm in	Rolling Circum mm in	Load Index Speed Symbol	Infl. press. bar psi	Static	Recommend load, kg (lbs) Speed, km/h (mph) Constant load 10 6	20 12	30 19	40 25	50 31	Cyclic operation 10 6	15 9
650 75R32 CHO SB*	DW21B, DW20L	625 24.6	1810 71.3	857 33.7	5459 214.9	172A8/B	0.8	6440	4200	3440	3000	2800	2800	5040	4620
							12	14190	9250	7580	6610	6170	6170	11100	10180
							1.6	9660	6300	5170	4490	4200	4200	7560	6930
							23	21280	13880	11390	9890	9250	9250	16650	15260
							2	11020	7190	5890	5130	4790	4790	8620	7900
							29	24270	15840	12970	11300	10550	10550	18990	17400
							2.6	12830	8370	6860	5970	5580	5580	10040	9210
							38	28260	18440	15110	13150	12290	12290	22110	20290
							3.2	14490	9450	7750	6740	6300	6300	11340	10400
							46	31920	20810	17070	14850	13880	13880	24980	22910

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards