

FARMAX RC

FEATURES

- High lug angle at centre
- More overlap at centre

BENEFITS

- Better roadability
- Better stability

FEATURE

- Rounded shoulder

BENEFIT

- Soil and plant protection

FEATURE

- Deep tread pattern

BENEFIT

- Long service life




FEATURES

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

BENEFITS

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

MACHINERY



Tractor

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	PR Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10 6	25 16	40 25	50 31	65 40	70 43
300/95R46 (12.4R46)	W9	300	1738	815	5242	148D/ 151A8	0.8	1300	1700	1340	1240	1190	1130	1030
							11.6	2860	3740	2950	2730	2620	2490	2270
	1.8						2090	2730	2160	1990	1910	1820	1660	
	26.1						4600	6010	4760	4380	4210	4010	3660	
	2.6						2590	3380	2670	2460	2360	2250	2050	
	37.7						5700	7440	5880	5420	5200	4960	4520	
	3.4						3290	4290	3390	3130	3000	2860	2600	
	49.3						7250	9450	7470	6890	6610	6300	5730	
	4						3620	4730	3730	3450	3310	3150	2870	
	58						7970	10420	8220	7600	7290	6940	6320	

All tires confirms ETRTO T&RA & STRO standards