

FARMAX R80

FEATURE

- Higher angle and lug overlap at centre

BENEFIT

- Better roadability

FEATURE

- R1-W tread depth

BENEFIT

- Longer tyre life

FEATURE

- Wider tread
- Larger inner volume

BENEFIT

- Reduced soil compaction



FEATURE

- Rounded shoulder

BENEFIT

- Reduced damage to soil and crop


FEATURE

- Lower angle at shoulder

BENEFIT

- Superior traction

MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars Load Index	Infl.Press	Recommend Load, kg (lbs)					
		SW	OD					Tractor application					
		mm/in	mm/in					mm/in	mm/in	Static	10 6	20 12	30 19
380/80R38	W11 W12 W13	380 15	1573 61.9	726 28.6	4793 188.7	152A8/B	0.8	3200	2090	1710	1490	1390	1390
							12	7050	4600	3770	3280	3060	3060
							1.8	5150	3360	2760	2400	2240	2240
							2.6	11340	7400	6080	5290	4930	4930
							2.6	6350	4140	3390	2950	2760	2760
							3.8	13990	9120	7470	6500	6080	6080
							3.4	7430	4850	3970	3460	3230	3230
							4.9	16370	10680	8740	7620	7110	7110
							4	8170	5330	4370	3800	3550	3550
5.8	18000	11740	9630	8370	7820	7820							

All tires confirms ETRTO T&RA & STRO standards