

# FARMAX R65

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity

**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance


**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	Infl.Press	Recommend load, kg (lbs) Speed, km/h (mph)							
				SW	OD				Field Operation	Non cyclic operation				Cyclic operation		
				mm/in	mm/in					25	40	50	65	bar	10	15
										16	25	31	40	psi	6	9
650/ 65R38	157D	TL	DW20B	645 25.4	1823 71.8	826 32.5	5527 217.6	0.8	3160	3260	3010	2890	2750	1	4680	4260
								20	6960	7180	6630	6370	6060	15	10310	9380
								1	3600	3710	3430	3290	3130	1.3	5320	4850
								23	7930	8170	7560	7250	6890	18	11720	10680
								1.3	4200	4330	4000	3830	3650	1.6	6210	5660
								29	9250	9540	8810	8440	8040	24	13680	12470
								1.6	4740	4890	4520	4330	4125	2	7010	6390
								35	10440	10770	9960	9540	9090	29	15440	14070

All tires confirms ETRTO T&RA & STRO standards