

FLOATMAX RT

FEATURE
Directional Lug

BENEFIT
Higher traction,
Comfortable ride

FEATURE
Robust Centre Blocks

BENEFIT
Low noise and smooth
run on hard surface

FEATURE
Steel belted radial
construction

BENEFIT
Protection from
Punctures




FEATURE
Rounded Shoulder

BENEFIT
Less damage to
soil & crops

FEATURE
Interconnected
grooves

BENEFIT
Better self cleaning
properties

MACHINERY



Trailer

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)										
		SW	OD	Radius				Speed, km/h (mph)										
		mm	mm	mm	mm	Speed		MIXED APPLICATION										
		in	in	in	in	Symbol		Static	10	30	40	50	65					
						bar		6		19		25		31		40		
650/50 R 22.5 RT	AG20.00	645	1230	559	3725	163D	0.8	4370	3420	2870	2580	2300	1900					
							12	9630	7530	6320	5680	5070	4190					
							2	7480	5850	4910	4420	3930	3250					
							29	16480	12890	10810	9740	8660	7160					
							3	9480	7420	6220	5600	4990	4120					
							44	20880	16340	13700	12330	10990	9070					
							4.0	11210	8780	7360	6630	5900	4875					
58	24690	19340	16210	14600	13000	10740												